



PRISMJET[®] Wall•TEX[™]

- 4.0 mil premium white matte coated polyester fabric with a clear, repositionable, removable wall adhesive
- Superior conformability and adhesion, even on textured walls
- Ideal for full bleed, large format contour-cut wall graphics
- Compatible with eco-solvent, solvent, Latex & UV inkjet printers



PROPERTIES

- **Face Stock**
4 mil matte white, polyester fabric
- **Adhesive**
Low tack clear acrylic removable and repositionable adhesive. Adhesion to standard test panels: 4 -12 oz. /in.*
Adhesive thickness: 0.8 -1.2 mil
- **Liner**
6.7 mil 90# liner with superior layflat properties
- **Applications**
Temporary application of decals and graphics to most painted interior walls, including gloss, semi-gloss, and flat finishes
- **Temperature Ranges**
Minimum application: 40°F
Service temperature range: -40°F to +200 F
- **Available Sizes**
48" and 54" x 100 ft rolls

PrismJET 250 WallTEX[™] is a 4.0 mil premium white matte coated polyester fabric with a clear, removable, pressure sensitive acrylic adhesive backed by a 90# stay flat liner. The combination of fabric and adhesive allows clean removability and repositioning of this product from normal wall surfaces. The 90# digital release liner provides excellent stability for processing using standard solvent, eco-solvent and UV curable inks common to wide format digital printers.

PrismJET 250 is designed for long term and temporary application of decals and graphics to most painted interior walls. Graphics are considered removable for up to two years. For repositionable decals, application with medium tack transfer tape is recommended to prevent stretching the face film. The surface should be smooth and clean prior to application, although SignWarehouse product testing has established that WallTEX[™] produces good short and long term adhesion even on slightly textured surfaces that pose problems for adhesive backed vinyl products.



SIGNWarehouse.com 800-699-5514

2614 Texoma Drive Denison, TX 75020

* Tested according to PSTC-101 Method A procedures with 24 hour dwell at 70°F and 50% relative humidity. Typical values. Individual values may vary. Bond to wall surfaces may vary. Test thoroughly before production.

PrismJET 250 WallTEX Fabric